



PATENT ABSTRACTS OF JAPAN

(11) Publication number: 2007101027 A

(43) Date of publication of application: 19.04.07

(51) Int. Cl.	F24C 15/10	20060101
	F24C 3/08	20060101
	F24C 3/02	20060101
	F23D 14/06	20060101
	F23D 14/02	20060101

(21) Application number: 2005289780

(22) Date of filing: 03.10.05

(71) Applicant: MATSUSHITA ELECTRIC IND CO LTD

(72) Inventor: SHIMADA RYOJI  
YANAGISAWA TADASHI  
SASADA KATSUMI

(54) COOKING STOVE

(57) Abstract:

PROBLEM TO BE SOLVED: To achieve a good combustion state and high heat efficiency by using a burner forming the flame circling at its upper face, with respect to a cooking stove applying gas or oil as its fuel.

SOLUTION: As an air passage 21 for communicating a part between an inner peripheral edge portion of a base 7 of a trivet 8 and a shielding body 5 to a part between an outer peripheral lower end portion of the base 7 to an upper face of a top plate 2 is formed between the base 7 and the shielding body 5, the combustion air can be effectively diffused into the flame 13, thus the cooking stove 1 capable of ensuring high heat efficiency while reducing emission of CO, and improving its cleanability by reducing getting stuck of cooking liquid, can be provided.

COPYRIGHT: (C)2007,JPO&INPIT

