P-60307/EP1 KKM Ref.: 30 600 SO

Auxiliary Request 10a - Clean

5 1. Nozzle (1) for a vacuum cleaner (2), the nozzle (1) comprising:

10

15

20

25

- a rotatable member (3) for picking up particles from a surface to be cleaned, the rotatable member (3) being arranged around a longitudinal axis (10), and
- a cleaning arrangement for removing articles entangled to the rotatable member (3), the nozzle being characterized in that it further comprises:
- a nozzle cover (12) that at least partly is made of transparent material such that the rotatable member (3) may be visible through the nozzle cover (12).

wherein the cleaning arrangement comprises a cleaning member (5) and a support surface (4) provided on a radially projecting member of the rotatable member (3),

wherein the cleaning member (5) is movable between a resting position in which the cleaning member (5) is arranged at a distance from the support surface (4) and a cleaning position, and

wherein the cleaning member (5) comprises a resilient sheet member (5a) capable of providing a resilient contact with at least one segment (4a) of the at least one support surface (4) in the at least one cleaning position during rotation of the rotatable member (3).

2. The nozzle (1) according to claim 1, wherein the support surface (4) is provided on at least one radially projecting member (13) of the rotatable member (3), and

wherein the cleaning position is in the vicinity of the rotatable member in which the cleaning member (5), during rotation of the rotatable member (3), co-operates with at least one segment (4a) of the support surface (4) to remove any entangled articles from the rotatable member (3).

- 30 3. The nozzle (1) according to of claim 2, wherein the at least one radially projecting member (13) is helically arranged along a longitudinal axis (10) of the rotatable member (3).
- 4. The nozzle (1) according to claims 2 or 3, wherein the cleaning member (5) is moved from the resting position to the at least one cleaning position by applying a pressing force to a push button (6) provided on the nozzle (1) at a surface turned towards a user.